

# GFCI receptacle

## Features

- SafeLock™ protection: if critical components are damaged and ground fault protection is lost, power to receptacle is disconnected
- Prevents line-load reversal miswire: no power to the face or downstream receptacles if wired incorrectly
- Exceeds UL943 voltage surge requirements; survives 100x the required UL 3kA/6kV voltage surge test cycles
- FSUL Listed (Federal Specification WC596)
- Trip indicator light (red LED)
- Side or internal screw-pressure-plate back wire with #10 – #14 AWG solid or stranded copper wire
- Two back wire holes per terminal
- Ground screw has a back wire clamp for easy installation
- Mounting screws are shipped captive in the device and wall plate for easier installation
- High impact-resistant thermoplastic construction
- Extra-long strap
- Button colors match the device face
- Dual direction test and reset buttons
- Class A rated GFCI
- Tri-drive screws
- GFCI's with auto-ground assure a positive ground to metal box

## Specifications

### General

- Color: ivory

### 3rd party compliance

- CSA listing info: C22.2 No. 42 and 144
- CSA standard: yes
- cULus: yes
- Federal Spec: yes
- Fed Spec Number: WC596
- UL listing no: UL498
- UL Standard: yes
- UN SPS C: 39121614

### Dimensions

- Depth: 0.98"
- Height: 4.20"
- Width: 1.72"

### Technical information

- Amps: 15 Amp
- Volts: 125
- Volts A C: 125
- Grade type: specification

