

# Disconnect switch Cabinet Unit Heater

## □ 120V, 15A

Single pole switch with grounded terminals, has a thermoplastic toggle and frame. It has a smooth, quiet toggle action and is made with high-impact resistant construction.

### Features

- Side wire #12 and #14 AWG
- Push wire #14 AWG
- Tri-drive ground, terminal, and mounting screws
- Easy-access green hex head ground screw

## □ 200V, 15A

Double pole switch with grounded terminals, has a thermoplastic toggle and frame. It has a smooth, quiet toggle action and is made with high-impact resistant construction.

### Features

- Side wire #12 and #14 AWG
- Push wire #14 AWG
- Tri-drive ground, terminal, and mounting screws
- Easy-access green hex head ground screw



## Specifications

### General

- Type: toggle
- Number of poles: 1-way
- Special features: self-grounding

### 3rd party compliance

- CSA listing info: 140597
- CSA standard: yes

- UL listing no: 20
- UL Standard: yes
- UL 498

### Technical information

- Amps: 15 Amp
- Volts: 120VAC



### 3rd party compliance

- UL Listed, File Number E140597, Standard UL20, General Use Snap Switches
- Federal Specification WS896
- cULus Listed, File Number LR17446, Standard CSA-C22.2 No. 111, General Use Snap Switches
- Conforms to NEMA WD-1 and WD-6

### Performance

Electrical	
Dielectric withstand voltage	1500V minimum
Maximum working voltage	277VAC
Overload minimum	4.8 times rated current for 100 cycles
Temperature rise	30 °C maximum at rated current
Maximum continuous current	277VAC
Endurance	50,000 cycles min., resistive, inductive, tungsten filament lamp load (fed spec)
Mechanical	
Terminal accommodations	#14 AWG – #10 AWG
Environmental	
Flammability	UL94 V2
Operating temperature	Max. continuous +115 °C, min. -40 °C