

# 0-25% motorized outside air damper Cabinet Unit Heater



## Features

### Models RF and RS only

- Operational at 0% or 25% outside air
- Furnished with a 120V/60/1 synchronous motor that is wired to the blower to automatically open the damper when the fan starts
- When the power is off or interrupted, the damper returns to the closed position
- Located in bottom of floor mounted units only
- Damper motor always on right side when viewing unit from front side
- All listed dimensions are approximate and are subject to change without notice
- Modifications to the product specifications must be accepted by Zehnder Rittling at its base office

Unit size	A	B	C	D
02	38-3/16	22-3/8	24	18-5/8
03	44-3/16	28-3/8	30	18-5/8
04	50-3/16	34-3/8	36	23-5/8
06	62-3/16	46-3/8	48	23-5/8
08	68-3/16	52-3/8	54	33-5/8
10	76-3/16	60-3/8	62	33-5/8
12	86-3/16	70-3/8	72	33-5/8

## Specifications

- 20-gauge galvanized steel
- Foam gasket seal
- Voltage: 120V/60Hz/1Ph
- Power: 5W
- Speed: 60 RPH
- Run torque: 40 in.-oz. (minimum)
- Reset torque: 13 in.-oz. (minimum)
- Insulation: class B

